# **Material Safety Data Sheet**

### EX-Series® FRP Composite Products

### Section 1 - Product & Company Identification

Company: Treadwell Group Pty Ltd ABN: 40 140 529 200

Address: 58 Deeds Road, North Plympton, South Australia 5037

**Phone:** 1800 246 800 Fax: 1300 763 521

**Poisons Information Centre:** Australia 131 126 New Zealand 0800 764 766

**Recommended Use:** Structural Component

### Section 2 - Hazard(s) Identification

Company: Treadwell Group Pty Ltd ABN: 40 140 529 200

**Address:** 58 Deeds Road, North Plympton, South Australia 5037

**Phone:** 1800 246 800 Fax: 1300 763 521

Classification: In accordance with 29 C.F.R § 1910.12000, this product is an "article" and

therefore not subject to the HCS 2012 SDS and labeling requirements. The information presented is for potential end use grinding, sanding,

cutting, or other mechanical work of this product.

Signal Word: Warning
Pictogram: None

**Hazard Statement:** May form combustible dust concentrations in air

**Precautionary Statements:** None

**Hazards Not Otherwise** 

Classified:

The grinding, drilling, sanding, cutting, or other mechanical working of this product may generate dusts that could act as a mechanical irritant to skin, eyes and upper respiratory system. Vapors or products of thermal degradation

generated by cutting or grinding may aggravate or cause respiratory conditions.

### Sections 3 - Composition/Information on Ingredients

Chemical ComponentCAS NumberPercentPolymerised ResinNone30%-75%Fibreglass65997-17-325%-70%Quartz Silica Sand (Present Within Anti-slip Gritted Products Only)14808-60-71%

TREADWELL EX-Series®

# **Material Safety Data Sheet**

### **Section 4 - First Aid Measures**

**Routes of Entry:** Inhalation, skin, and ingestion

**Sign & Symptoms of Exposure:** Temporary irritation and itching to skin or eyes. Scratchiness or burning of

the nose and/or throat if exposed to large amount of airborne dust from

cutting or machining.

**Emergency & First Aid Procedures:** Wash skin well without rubbing. For eyes, use a sterile solution and flood

the eye area. Change clothing after exposure. Apply antiseptic to any

abraded skin area.

### **Section 5 - Fire Fighting Measures**

**Extinguishing Media:** Water: Foam/Type A,B, or C Extinguishers

Special Firefighting Procedures: Use Self-Contained Breathing Apparatus (SCBA) with full face mask

operated in pressure mode.

**Unusual Fire & Explosion Hazards:**Burning FRP a complex mixture of solid, liquid, particulate and gasses.

Carbon monoxide and other organic compounds may be given off. Avoid generating dust: fine dust dispersed on air on sufficient concentrations, and in the presence of an ignition source is a potential dust explosion

hazard.

### Section 6 - Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures:

Non-sparking tools should be used. Avoid dispersal of dust in the air (i.e. clearing dust surfaces with compressed air).

Methods and materials for containment and cleaning up:

Dust deposits from fabrication should not be allowed to accumulate on surfaces, as these may from an explosive mixture if they are released into

atmosphere in sufficient concentration.

### Section 7 - Handling and Storage

**Handling:** Use personal protection equipment to minimize skin, respiratory and eye

exposure to dust and fumes when cutting or grinding product. Do not rub or scratch skin if dust particles have accumulated on exposed skin. Wash all exposed skin areas thoroughly after cutting or grinding. Launder

clothing separately and frequently to prevent skin exposure.

**Fabrication of Product:** Minimize dust generation and accumulation. Routine housekeeping

should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions,

such as electrical grounding and binding, or inert atmospheres.

**Storage:** No special storage conditions exist.

# **Material Safety Data Sheet**

| Section 8 - Exposure Controls/Personal Protection |  |  |
|---|--|--|
| Occupational Expose Limits                        |  | Value  |
| OSHA PEL<br>ACGIH TLV                             |  | 150mg /m³ (Nuisance Dust) Total<br>10mg / m³ (Nuisance Dust) Total   |
| Respiratory Protection:                           | An approved dust mask for dusts and mists with PEL not less than $0.1 mg/M^3$ when cutting or grinding.  |  |
| Protection Gloves:                                | Wear cloth gloves when handling product to prevent cuts, scratches, or abrasions.  |  |
| Eye Protection:                                   | Wear protective eyewear with side shield or ventilated goggles when cutting or grinding.   |  |
| Other Protective<br>Equipment:                    | Barrier cream and long sleeve shirts with closed collars, long pants or protective clothing may be worn to prevent dust exposure when cutting or grinding product. |  |
| Ventilation:                                      | ventillation a<br>contain explo<br>deficient envi<br>dust collector<br>prevent the e   | nended that all dust control equipment such as local exhaust and material transport systems involved in handling of this product osion relief vents, an explosion suppression systems, or an oxygen ronment. Ensure that dust-handling systems (such as exhaust ducts, rs, vessels, and processing equipment) are designed in a manner to escape of dust into the work area. (i.e., there is no leakage from the Use only appropriately classified electrical equipment and powered cks. |

| Property                                | Measurement:   |
|---|----------------|
| Appearance:                             |                |
| Physical State                          | Solid article  |
| Color                                   | Various Colors |
| Odor                                    | Low to none    |
| Odor Threshold                          | N/A            |
| рН                                      | N/A            |
| Melting Point/Freezing Point            | N/A            |
| Initial Boiling Point                   | N/A            |
| Flash Point                             | N/A            |
| Evaporation Rate                        | N/A            |
| Flammability                            | N/A            |
| Upper/Lower Flammability Limits         | N/A            |
| Vapor Pressure                          | N/A            |
| Vapor Density                           | N/A            |
| Relative Density                        | 1.5 - 2.0      |
| Solubility                              | Not applicable |
| Partition Coefficient: n-ocatnol /water | Not applicable |
| Auto-Ignition Temperature               | Not applicable |
| Decomposition Temperature               | Not applicable |

TREADWELL EX-Series®

# **Material Safety Data Sheet**

### Section 10 - Stabitlity and Reactivity Data

Stability: Stable

**Conditions to Avoid:**Sources of ignition, sparks, or flames, extremely high

temperatures

**Incompatibility:** Strong oxidizing acid

Hazardous Decomposition or Byproducts: Not applicable

**Hazardous Polymerisation:** Will not occur

### Section 11 - Toxicological Information

**Routes of Exposure:** 

Inhalation: Nuisance dust from machining can cause irritation.

Eye: Nuisance dust from machining can cause irritation.

Skin: Nuisance dust from machining can cause irritation.

Ingestion: N/A

Delayed and Immediate Effects: N/A

Acute Toxicity: N/A

**Carcinogenicity Status:** 

National Toxicology Program (NTP) N/A

International Agency for Research on Cancer (IARC) N/A

**OSHA** N/A

### **Section 12 - Ecological Information**

**Ecotoxicity:** No data

Persistence and Degradability:

Bioaccumulative Potential:

No data

Mobility in Soil:

No data

Section 13 - Disposal Considerations

**Waste Disposal Method:** Control and collect any dust generated in sturdy containers to

prevent dispersal. Dispose of in accordance with all federal, state, and local regulations. Generally, the dust is not

considered a hazardous waste.

TREADWELL EX-Series®

# **Material Safety Data Sheet**

### **Section 14 - Transport Information**

Shipping Name: Not regulated

Shipping Symbols: N/A

Hazard Class: Not hazardous

ID No:

Packing Group:

Not determined

Label:

Not required

Special Provisions: None

### Section 15 - Regulatory Information

**Environmental Regulations:** 

RCRA:

CERCLA:

Not listed

SARA 311/312 Codes:

None

SARA 313: None above de minimis quantity

### Section 16 - Other Information

**Refer to NFPA 654:** Standard for the Prevention of Fire and Dust Explosions

from the Manufacturing, Processing, and Handling of

Combustible Particulate Solids, for safe handling.

**HMIS:** Health = 0

Fire = 1

Reactivity = 0

**Issue Date:** 27/09/2017

We believe that the above information is valid and reliable. The information, however, is provided without any representation of warranty, expressed or implied, regarding the accuracy of correctness. The conditions of methods of handling, storage, use, cutting, grinding, disposal, or other use of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use, cutting, grinding, disposal, or any other use of this product.